## (19) World Intellectual Property **Organization**

International Bureau



## 

(43) International Publication Date 6 January 2005 (06.01.2005)

PCT

## (10) International Publication Number WO 2005/000539 A1

(51) International Patent Classification<sup>7</sup>:

B26B 19/38

(21) International Application Number:

PCT/IB2004/050989

(22) International Filing Date: 24 June 2004 (24.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03101924.3

27 June 2003 (27.06.2003)

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BEUGELS, Johannes [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). BARON, Sint [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN POM-MEREN, Jascha [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). HAMER, Bas [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


- (74) Agent: BOS, Kornelis, S.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

[Continued on next page]

(54) Title: SHAVER, SHAVING HEAD AND METHOD OF CLEANING A HAIR CHAMBER OF A SHAVER



(57) Abstract: A shaver comprises a shaving head (4; 104) with a screen (6) having an internal surface (7), an external surface for contacting a skin to be shaved, and hair-receiving openings (8, 9), and a cutter (3) having at least one cutting edge (5) movable along the internal surface (7) of the screen (6) by means of a drive structure (44; 125) that includes a motor. The cutting edge (5) cooperates with the screen (6) for cutting off hairs projecting through the hair-receiving openings. Behind the hair-receiving openings (8, 9) a hair chamber (13; 113; 213; 313) is located. The shaver is equipped with one or more liquid displacement impellers (15; 115; 215; 315) for displacing liquid through the hair chamber (13, 113, 213, 313). The impellers (15, 115, 215, 315) are each connected to the drive structure (44; 125) for driving the movement of the impeller (15; 115; 215; 315) for cleaning the hair chamber (13; 113; 213; 313).





For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.